

# Portable Electric Torque Wrench Pumps

▼ Shown: PMU-10427



## PMU Series



Reservoir Capacity:

**0.5 gal.**

Flow at 10,000 psi:

**20 in<sup>3</sup>/min.**

Motor Size:

**0.5 hp**

Maximum Operating Pressure:

**10,000 and 11,600 psi**

- Powerful two-speed pump is lightweight and easy to carry
- Standard heat exchanger package keeps pump cool under extreme use
- Glycerine filled gauge with scales reading in psi and bar
- Transparent overlays in Ft.lbs and Nm for all Enerpac torque wrenches provide a quick torque reference
- Universal motor for a high power-to-weight ratio; generates full pressure on as little as 50% of the rated line voltage
- Adjustable pressure relief valve for accurate torque adjustments and precise repeatability



### Pump Ratings

-Q suffix pumps are for 10,000 psi torque wrenches, and include spin-on couplers. PMU10427 and PMU10422 are for use with Enerpac SQD and HXD 11,600 psi torque wrenches, and include polarized locking safety couplers.



### Twin Torque Wrench Hoses

Use Enerpac THQ-700 series twin hoses with 10,000 psi pumps, or use THC-700 series twin hoses with 11,600 psi pumps.

19.5 feet long, 2 hoses	<b>THQ-706T</b>
39 feet long, 2 hoses	<b>THQ-712T</b>
19.5 feet long, 2 hoses	<b>THC-7062</b>
39 feet long, 2 hoses	<b>THC-7122</b>

### ▼ PERFORMANCE CHART

For Use With Torque Wrenches		Maximum Pressure Rating (psi)		Oil Flow Rate (in <sup>3</sup> /min)		Model Number	Useable Oil Capacity (gal)	Electric Motor	Dimensions L x W x H (in)	Weight (lbs)
		1 <sup>st</sup> stage	2 <sup>nd</sup> stage	1 <sup>st</sup> stage	2 <sup>nd</sup> stage					
S1500	W2000	700	10,000	200	20	<b>PMU-10427-Q</b>	.50	115V- 1 ph -50/60Hz	17 x 11 x 15	53
S3000	W4000	700	10,000	200	20	<b>PMU-10422-Q</b>	.50	230V- 1 ph -50/60Hz	17 x 11 x 15	53
SQD-25-I	HXD-30	700	11,600	200	20	<b>PMU-10427</b>	.50	115V- 1 ph -50/60Hz	17 x 11 x 15	53
SQD-50-I	HXD-60	700	11,600	200	20	<b>PMU-10422</b>	.50	230V- 1 ph -50/60Hz	17 x 11 x 15	53