

# LIGHT DUTY SERIES

RIGGERS KITS AND SETS CAPACITIES: 3 AND 8 TONS

KIT / SET CAPACITY (TONS)	ROLLER CAPACITY (TONS)	KIT PRODUCT NUMBER	SET PRODUCT NUMBER	KIT / SET INCLUDES (All KITS include steel cases) Steel Case Kit Box KB-D1: 16" (406mm) x 12.375" (314) x 4.44" (113mm)	WEIGHT	
					lbs.	kgs.
3	0.75	KRS-3-4S		(4) 0.75-SP Rollers; (2) 3-KH Kit Size Handles	55	25
3	0.75		RS-3-4S	(4) 0.75-SP Rollers, (2) H36T 36" Handles	52	24
3	0.75	KRS-3-2S/2R		(2) 0.75-SP Rollers, (2) 0.75-RP Rollers, (2) 3-KH Kit Size Handles	55	25
3	0.75		RS-3-2S/2R	(2) 0.75-SP Rollers, (2) 0.75-RP Rollers, (2) H36T 36" Handles	52	24
8	2	KRS-8-4S		(4) 2-SP Rollers, (2) 8-KH Kit Size Handles	85	39
8	2		RS-8-4S	(4) 2-SP Rollers, (2) H36T 36" Handles	76	35
8	2	KRS-8-2S/2R		(2) 2-SP Rollers, (2) 2-RP Rollers, (2) 8-KH Kit Size Handles	85	39
8	2		RS-8-2S/2R	(2) 2-SP Rollers, (2) 2-RP Rollers, (2) H36T 36" Handles	76	35



**HILMAN ROLLERS DELUXE KITS** or **PREPACKAGED COMPLETE SETS** are ideal for all kinds of heavy equipment moving, machinery installation and maintenance. Kits include everything needed to make those heavy moves: (4) professional quality Swivel-Locking Rollers\* and two full-length Steering Handles in a sturdy, heavy gauge steel storage case. Complete sets contain the same rollers and handles but are provided without the kit box. \*Swivel-Locking Rollers not available in sizes smaller than 3.75 tons each

## STEEL CHAIN-ACTION ROLLERS MOVE EQUIPMENT OVER ORDINARY FLOORS

**OUR MOST POPULAR MODELS**



**EASY AND SAFE TO USE!** Just lift the load, set the Rollers, and move. The recirculating chains on the **HILMAN ROLLERS** provide controllable heavy moving, right on ordinary concrete floors. Fully directional swivel tops allow equipment positioning in the tightest quarters. The 3 and 8 ton Kits and Sets feature Swivel Padded Rollers. The 15 ton and higher Kits and Sets are available with your choice of Swivel-Locking Padded Rollers or Rollers with Swivel-Locking Diamond steel grid tops and loose Preload Pads.

# FT SERIES

DELUXE KIT CAPACITIES: 15-60 TONS

COMPLETE SET CAPACITIES: 15-200 TONS

KIT / SET CAPACITY (TONS)	ROLLER CAPACITY (TONS)	KIT PRODUCT NUMBER	SET PRODUCT NUMBER	KIT / SET INCLUDES (All KITS include steel cases) Steel Case Kit Box KD-D2: 27.75" (705mm) x 14.75" (375mm) x 9.63" (245mm)	WEIGHT	
					lbs.	kgs.
15	3.75	KRS-15-SLP		(4) 3.75-SLP Rollers; (2) KDH48F Handles	203	92
15	3.75		RS-15-SLP	(4) 3.75-SLP Rollers; (2) H36F 36" Handles	156	71
15	3.75	KRS-15-SLD		(4) 3.75-SLD Rollers; (4) P-1 Preload Pads; (2) KDH48F Handles	203	92
15	3.75		RS-15-SLD	(4) 3.75-SLD Rollers; (4) P-1 Preload Pads; (2) H36F 36" Handles	156	71
30	7.5	KRS-30-SLP		(4) 7.5-SLP Rollers; (2) KDH48F Handles	215	98
30	7.5		RS-30-SLP	(4) 7.5-SLP Rollers; (2) H48F 48" Handles	172	78
30	7.5	KRS-30-SLD		(4) 7.5-SLD Rollers; (4) P-1 Preload Pads; (2) KDH48F Handles	215	98
30	7.5		RS-30-SLD	(4) 7.5-SLD Rollers; (4) P-1 Preload Pads; (2) H48F 48" Handles	172	78
40	10	KRS-40-SLP		(4) 10-SLP Rollers; (2) KDH48F Kit Size Handles	219	99
40	10		RS-40-SLP	(4) 10-SLP Rollers; (2) H48F 48" Handles	176	80
40	10	KRS-40-SLD		(4) 10-SLD Rollers; (4) P-1 Preload Pads; (2) KDH48F Handles	219	99
40	10		RS-40-SLD	(4) 10-SLD Rollers; (4) P-1 Preload Pads; (2) H48F 48" Handles	176	80
60	15	KRS-60-SLP		(4) 15-SLP Rollers; (2) KDH48F Kit Size Handles	255	116
60	15		RS-60-SLP	(4) 15-SLP Rollers; (2) H48F 48" Handles	212	96
60	15	KRS-60-SLD		(4) 15-SLD Rollers; (4) P-1 Preload Pads; (2) KDH48F Handles	259	117
60	15		RS-60-SLD	(4) 15-SLD Rollers; (4) P-1 Preload Pads; (2) H48F 48" Handles	216	98
120	30		RS-120-SLP	(4) 30-SLP Rollers; (2) H60F 60" Handles	542	256
120	30		RS-120-SLD	(4) 30-SLD Rollers; (4) P-2 Preload Pads; (2) H60F 60" Handles	540	245
200	50		RS-200-SLP	(4) 50-SLP Rollers; (2) H60F 60" Handles	834	378
200	50		RS-200-SLD	(4) 50-SLD Rollers; (4) P-2 Preload Pads; (2) H60F 60" Handles	848	385

# FT SERIES

## INDIVIDUAL ROLLER SPECIFICATIONS

	CAPACITY (TONS)	PRODUCT NUMBER	TOP STYLE	HEIGHT		WIDTH*		LENGTH		WEIGHT		CONTACT ROLLS
				in	mm	in	mm	in	mm	lb	kg	
<b>SLP</b>	3.75*	3.75-SLP	SWIVEL LOCKING PADDED	5	127	5-3/4	146	10-1/2	267	34	15	5
	7.5*	7.5-SLP		5-1/4	133	5-3/4	146	10-1/2	267	38	17	5
	10*	10-SLP		5-1/4	133	5-3/4	146	10-1/2	267	38	17	5
	15	15-SLP		5-1/8	130	6-3/8	162	12-3/4	324	49	22	5
	30*	30-SLP		8	203	8	203	15	381	122	55	5
	50*	50-SLP		8-15/16	227	8	203	21	533	193	88	7
<b>SLD</b>	3.75*	3.75-SLD	SWIVEL LOCKING WITH DIAMOND STEEL GRID	4-3/4	121	5-3/4	146	10-1/2	267	34	15	5
	7.5*	7.5-SLD		5	127	5-3/4	146	10-1/2	267	37	17	5
	10*	10-SLD		5	127	5-3/4	146	10-1/2	267	37	17	5
	15	15-SLD		4-7/8	124	6-3/8	162	12-3/4	324	49	22	5
	30	30-SLD		7-1/32	179	8	203	15	381	118	54	5
	50	50-SLD		8-1/16	205	8	203	21	533	189	86	7
<b>SLS</b>	3.75*	3.75-SLS	SWIVEL LOCKING WITH SMOOTH STEEL	4-5/8	117	6	152	10-1/2	267	35	16	5
	7.5*	7.5-SLS		4-7/8	124	6	152	10-1/2	267	38	17	5
	10*	10-SLS		4-7/8	124	6	152	10-1/2	267	38	17	5
	15	15-SLS		4-3/4	121	6-3/8	162	12-3/4	324	50	23	5
	30	30-SLS		7-15/16	202	8	203	15	381	119	54	5
	50	50-SLS		7-15/16	202	8	203	20-7/8	530	191	87	7
<b>SP</b>	.75	.75-SP	SWIVEL PADDED	3-5/16	84	3-5/8	92	6-1/2	165	9	4	5
	2	2-SP		3-15/16	100	4-1/8	105	6-1/2	165	15	7	4
<b>RP</b>	.75	.75-RP	RIGID PADDED	3-1/8	79	3-5/8	92	6-1/2	165	9	4	5
	2	2-RP		3-5/8	92	4-1/8	105	6-1/2	165	15	7	4
	3.75*	3.75-RP		4-3/16	106	5-3/4	146	10-1/2	267	29	13	5
	7.5*	7.5-RP		4-7/16	113	5-3/4	146	10-1/2	267	33	15	5
	10*	10-RP		4-7/16	113	5-3/4	146	10-1/2	267	33	15	5
	15	15-RP		4-5/16	110	6-3/8	162	12-3/4	324	42	19	5
<b>RD</b>	3.75*	3.75-RD	RIGID WITH STEEL SPIKES	4-1/16**	103	5-5/8	143	10-1/2	267	29	13	5
	7.5*	7.5-RD		4-5/16**	110	5-5/8	143	10-1/2	267	32	15	5
	10*	10-RD		4-5/16**	110	5-3/4	146	10-1/2	267	32	15	5
	15	15-RD		4-3/32**	104	6-3/8	162	12-3/4	324	38	17	5
	30*	30-RD		6-1/8**	156	8	203	15	381	105	48	5
	50*	50-RD		7-1/8**	181	8	203	21	533	176	80	7
<b>RS</b>	.75	.75-RS	RIGID WITH SMOOTH STEEL	2-3/4	70	3-5/8	92	6-1/2	165	8	4	5
	2	2-RS		3-1/4	83	4-1/8	105	6-1/2	165	15	7	4
	3.75*	3.75-RS		3-11/16	94	5-5/8	143	10-1/2	267	29	13	5
	7.5*	7.5-RS		3-15/16	100	5-5/8	143	10-1/2	267	32	15	5
	10*	10-RS		3-15/16	100	5-5/8	143	10-1/2	267	32	15	5
	15	15-RS		3-13/16	97	6-3/8	162	12-3/4	324	43	20	5
	30*	30-RS	5-3/4	146	8	203	15	381	105	48	5	
	50*	50-RS	6-3/4	171	8	203	21	533	176	80	7	

\* Width dimension of top exceeds roller frame width

\*\* Height to top of spike

## STEERING HANDLES with Safety Grips

	MODEL	FITS	FITS	DESCRIPTION	LENGTH		WEIGHT	
					in	mm	lb	kg
	3-KH	FT 3 ton Kits	Nyton 2 ton Kits	One Part Kit Size Handle	15	381	3	1
	8-KH	FT 8 ton Kits	Nyton 4 ton Kits	Two Part Kit Size Handle	30	762	6	3
	KDH48F	FT 15 - 60 ton Kits	Nyton 8 - 24 ton Kits	Two Part Kit Size Handle	48	1219	12	5
	H36F	FT 3.75 - 15 ton Rollers	Nyton 2 - 6 ton Rollers	One Part Handle	36	914	10	5
	H48F	FT 3.75 - 30 ton Rollers	Nyton 2 - 10 ton Rollers	One Part Handle	48	1219	12	5
	H60F	FT 3.75 - 50 ton Rollers	Nyton 2 - 10 ton Rollers	One Part Handle	60	1524	25	11